

BOOK 550 PAGE 176

SCHEDULE OF MACHINERY
COVERED BY LEASE AGREEMENT
BETWEEN

WHITIN MACHINE WORKS, LESSOR
WHITINSVILLE, MASS.

AND

J. P. STEVENS AND CO., INC., LESSEE

Dunearn Mills
Division of J. P. Stevens & Co., Inc.
Greenville, South Carolina

40- Whitin SUPERFLEX Spinning Frames, Model "F5", serial numbers 550601 to 550640 inclusive, 276 spindles each, 3-1/2" gauge, 2-1/4" diameter #2 Flange D.A. rings 3/8" deep in 2-1/2" diameter cast iron holders, with Jenckes traveler cleaners, #20 separators, triple shift Veeder-Root hank clocks with right angle mounting, Bijur system of lubrication, guard rails, roller bearing spindles with SKF HM3-37 bolster with bolster case slabbed for knee brakes, 10" diameter cylinders equipped with Fafnir anti-friction bearings, Whitin ball bearing tape tension pulleys, H & B umbrella type creel for double roving with 6 lines (3 on each side of frame) of 3/4" tubing in place of bottom deck boards, Climax regular duty ball bearing front top rolls covered with Accotex J-490, Whitin Type "R2" System of SUPER-DRAFT, case-hardened balloon control rings with doffing attachment, 1-1/4" back bottom rolls, Casablancas 36 mm cradles, to specifications dated March 23, 1955

20,000 Eclipse Bobbin Holders with brakes

Central System of Pneumafil Equipment--parts for frames only consisting of suction flutes, collecting header, collector box without motors and fans, extension elbows, elbow that connects carrier box to the header

40- Whitin SUPERFLEX Spinning Frames, Model "F5", serial numbers 550561 to 550600 inclusive, 276 spindles each, 3-1/2" gauge, 2-1/4" diameter #2 Flange D.A. rings 3/8" deep in 2-1/2" diameter cast iron holders, with Jenckes traveler cleaners, #20 separators, triple shift Veeder-Root hank clocks with right angle mounting, Bijur system of lubrication, guard rails, roller bearing spindles with SKF HM3-37 bolster with bolster case slabbed for knee brakes, 10" diameter cylinders equipped with Fafnir anti-friction bearings, Whitin ball bearing tape tension pulleys, H & B umbrella type creel for double roving with 6 lines (3 on each side of frame) of 3/4" tubing in place of bottom deck boards, Climax regular duty ball bearing front top rolls covered with Accotex J-490, Whitin Type "R2" system of SUPER-DRAFT, case-hardened balloon control rings with doffing attachment, 1-1/4" back bottom rolls, reverse twist arrangement, without bobbin holders, Casablancas 36 mm cradles, to specifications dated March 23, 1955

Central System of Pneumafil Equipment--parts for frames only consisting of suction flutes, collecting header, collector box without motors and fans, extension elbows, elbow that connects carrier box to the header.

Recorded April 13th, 1956 at 10:27 A.M. #9503