

d. The front end wall of building shall be constructed of eight (8) inch concrete block and four (4) inch face brick.

3. Inside partitions shall be provided to form two (2) toilet rooms, a storage closet six (6) by ten (10) feet, and an office space fifteen (15) by fourteen (14) feet. Office and toilet room framing shall be 2x6's 2' on center and covered with 3/8 inch sheetrock on one side only. The floor shall be concrete and shall be four (4) inches in thickness except for a space fourteen (14) feet wide and one hundred (100) feet long which shall be six (6) inches.

f. The roof structure shall be of wood trussed rafters as designed by Timber Engineering Company, Washington, D. C., and recommended for a span of fifty (50) feet.

g. Roof decking shall be 3/4 inch boards and roofing two hundred and ten (210) pound strip shingles.

h. No. ceiling shall be provided except in office and toilets.

i. Two thirteen (13) feet high by twelve (12) feet wide overhead wood doors shall be provided. Also one other outside door three (3) by seven (7) shall be provided. Four other inside doors to office, toilets and advertising storage shall be provided.

j. Eight steel windows 3-8 x 5-5 shall be built into the walls, and shall be of a ventilating type that opens outward.

k. A flue to accommodate an oil-burning space heater shall be provided in office.

l. A commode and lavatory with cold water only shall be provided in each of two toilet rooms. A cast iron floor drain with four-inch cast iron drain pipe shall be provided in floor.

m. All concrete block walls shall be painted with two (2) coats of Bondex. Doors and windows shall be painted with two (2) coats. Walls