

(continued)

LABORATORY EQUIPMENT

Hand forge, 22" -Champion
 Anvil, small
 Grindstone and metal stand
 Power hack saw -Homemade
 Small tools, freight and erection of machine shop equipment (Lot)

HUMIDIFIER AND MILL CLEANING SYSTEM

Atomizer heads -P. -C. (62 units)
 Supply boxes -P. -C. (2 units)
 Air outlets forecleaning (6 units)

Air compressor, 9" by 8" Class ERI, with 24" by 8' -6" storage tank and after cooler, No. 49091 -Ingersoll-Rand

Filter, 10" diam, by 30" high Triples pump
 Single cylinder pump used as stand-by (Lot)

Service pump and tank on mill -Goulds (Lot)

36" attic fan in penthouse in spinning room

Elevator, 57" by 52" platform, belted

Diesel engine, 3 cylinders, Model C, 180 hp, 257 rpm, Style VA, direct-connected to generator, Type D, Form D461, 3 phase, 60 cycle, 150 kva, 2300 volts, 37.5 amperes, 257 rpm, Serial No. 130431; exciter, belt-drive, Type CPB, Form 91, 15 kw, 125 volts, 1400 rpm, No. X 40421, Fairbanks-Morse; all on concrete foundation
 - (Lot)

Fuel banks, 8' -0" by 16' 0", with foundations, (Lot)

Air compressor, 4½ by 4½. 190 rpm, No. A512, Curtis; motor, 7½hp, 220 volts, 1200 rpm, No. 74425 -G.E.

Air receiver, 20" by 5' -6"
 Air receiver, 20" by 5' -0" (Lot)

Cooling tower

Switchboard, complete with voltage regulator, voltmeters, ammeters, oil switches, etc.

MOTORS AND POWER TRANSMISSION

All motors are 2300 volts, 3 phase, 60 cycles, unless otherwise noted, and are equipped with controls, bases, and pulleys

125 hp, 900 rpm, No. 108749, drives carding and spinning -G.E.

85hp, 720 rpm, No. 97540, drives, twisting, spooling, warping, speeders, and winders-G.E.

75 hp, 1200 rpm, drives pickers, 4 spinning frames, air compressor and pumps -G.E.

2 hp, 600 rpm, direct connected motor to 30" blower in motor-room

Oil switches, Type F, 100 amp., 2500 volts; and two switchboard panels Type ATL, 2300 volts, one pull switch on panel (2 units)

Slate panel, 22" by 36", recording volt meter chart, voltage indicator, 1 knife switch-G.E.

Transformer, 5kw, Type RC, Form P. primary volts 2300, 60 cycle, 6.6 amp., 2074000 -G.E.

Oil circuit breaker, Type FK-20-T-PST; rating of breaker, 200 amp., 2500 volts, overload coil amp. rating 200.; Cat.No. 167394, for street lights

Oil circuit breaker, Type FK -20-T-PST, rating of breaker, 2500 volts, 300 amp., overload coil amp. rating 250, under voltage release 110-550 V., 25-60 for house lights

1926